


Recessed Downlight

ZERN-Y01HD



3.000K 4.000K 5.000K 6.000K



Body Color Reflector Color


■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
12W	AC100-240V	50/60Hz	95Lm/W	1.140Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP20	15°/24°/38°	Die Casting Aluminium
20W	AC100-240V	50/60Hz	95Lm/W	1.900Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP20	15°/24°/38°	Die Casting Aluminium
50W	AC100-240V	50/60Hz	95Lm/W	4.750Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP20	15°/24°/38°	Die Casting Aluminium
80W	AC100-240V	50/60Hz	95Lm/W	7.600Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP20	15°/24°/38°	Die Casting Aluminium

Model : ZERN-Y01HD-12W




Dimension (mm)



Model : ZERN-Y01HD-50W




Dimension (mm)



Model : ZERN-Y01HD-20W




Dimension (mm)



Model : ZERN-Y01HD-80W



Dimension (mm)



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°