



DOWN LIGHT

ZERON
NEW LIGHT NEW LIFE

Recessed Downlight ZERN-H06S



3.000K 4.000K 5.000K 6.000K


■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
10W	AC100-277V	50/60Hz	100Lm/W	1.000Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium
20W	AC100-277V	50/60Hz	100Lm/W	2.000Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium
30W	AC100-277V	50/60Hz	100Lm/W	3.000Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium
40W	AC100-277V	50/60Hz	100Lm/W	4.000Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium

Model : ZERN-H06S-10W




Dimension (mm)



Model : ZERN-H06S-30W




Dimension (mm)




Model : ZERN-H06S-20W




Dimension (mm)



Model : ZERN-H06S-40W



Dimension (mm)



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

