



3.000K    4.000K    5.000K    6.000K

**ZERON**  
NEW LIGHT NEW LIFE

## Recessed Downlight

**ZERN-001LP**


### ■ Specification

| Daya (W) | Input Voltage | Frequency Amp | LED Efikasi | Total Lumen | CRI  | Temperatur Warna  | Proteksi | Beam Angle  | Material              |
|----------|---------------|---------------|-------------|-------------|--|-------------------|----------|-------------|-----------------------|
| 21W      | AC100-240V    | 50/60Hz       | 90Lm/W      | 1.890Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 28W      | AC100-240V    | 50/60Hz       | 90Lm/W      | 2.520Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 36W      | AC100-240V    | 50/60Hz       | 90Lm/W      | 3.240Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 48W      | AC100-240V    | 50/60Hz       | 90Lm/W      | 4.320Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 60W      | AC100-240V    | 50/60Hz       | 90Lm/W      | 5.400Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 80W      | AC100-240V    | 50/60Hz       | 90Lm/W      | 7.200Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K | IP20     | 15°/24°/36° | Die Casting Aluminium |

Model : ZERN-001LP-7W\*3




Dimension ( mm )



Model : ZERN-001LP-7W\*4




Dimension ( mm )



Model : ZERN-001LP-12W\*3




Dimension ( mm )



Model : ZERN-001LP-12W\*4




Dimension ( mm )



Model : ZERN-001LP-20W\*3




Dimension ( mm )



Model : ZERN-001LP-20W\*4



Dimension ( mm )



\* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°