



DOWNLIGHT

ZERON
NEW LIGHT NEW LIFE

Recessed Downlight ZERN-J02FSS



3.000K 4.000K 5.000K 6.000K


■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
28W	AC100-240V	50/60Hz	110Lm/W	3.080Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
40W	AC100-240V	50/60Hz	110Lm/W	4.400Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
48W	AC100-240V	50/60Hz	110Lm/W	5.280Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
72W	AC100-240V	50/60Hz	110Lm/W	7.920Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
80W	AC100-240V	50/60Hz	110Lm/W	8.800Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
120W	AC100-240V	50/60Hz	110Lm/W	13.200Lm	>80Ra Optional (>90Ra, >95Ra)	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium

Model : ZERN-J02FSS-7W*4




Dimension (mm)



Model : ZERN-J02FSS-18W*4




Dimension (mm)



Model : ZERN-J02FSS-10W*4




Dimension (mm)



Model : ZERN-J02FSS-20W*4




Dimension (mm)



Model : ZERN-J02FSS-12W*4




Dimension (mm)



Model : ZERN-J02FSS-30W*4



Dimension (mm)



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

