



DOWN LIGHT

ZERON
NEW LIGHT NEW LIFE

Recessed Downlight ZERN-S02CX

Honeycomb



Body Color



Reflector Color




■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
5W	AC100-240V	50/60Hz	110Lm/W	550Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
7W	AC100-240V	50/60Hz	110Lm/W	770Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
9W	AC100-240V	50/60Hz	110Lm/W	990Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
12W	AC100-240V	50/60Hz	110Lm/W	1.320Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium
15W	AC100-240V	50/60Hz	110Lm/W	1.650Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/6000K	IP65	15°/24°/38°/60°	Die Casting Aluminium


Model : ZERN-S02CX-5W



Dimension (mm)




Light Distribution Curve




Model : ZERN-S02CX-7W



Dimension (mm)




Light Distribution Curve




Model : ZERN-S02CX-9W



Dimension (mm)




Light Distribution Curve




Model : ZERN-S02CX-12W



Dimension (mm)




Light Distribution Curve




Model : ZERN-S02CX-15W



Dimension (mm)



Light Distribution Curve



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

